





Spot		Medium		Flood	
14°		25°		33°	
m	ø	m	ø	m	ø
1.0	0.24	1.0	0.37	1.0	0.55
2.0	0.48	2.0	0.75	2.0	1.10
3.0	0.73	3.0	1.12	3.0	1.65



A 131 B 101 C 114 (mm)



Saw instruction: ø 124 mm

## Amber mini COB 1500

### Technical specification

Down light with separated electronic gear and Chip on board. Improved color rendering index +90. High quality lenses with three different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight.

**Model and colors** Available in white, black and grey.

**Area of use** Down light for indoor applications.

### Technical data

Mains (input) voltage	220-240 V
Total weight	0,6 kg
Form of protection	IP 20, class III
Color temperature	3 000 K
Color rendering index (CRI)	90
Light source	LED
Operating position	360°/60°
Start time	Instant
Driver	Separate
Optics	PMMA
Beam spreads	Spot, Medium, Flood

Art no	Description	Color
253-500-10	Spot	White
253-500-20	Spot	Black
253-500-30	Spot	Grey
253-501-10	Medium	White
253-501-20	Medium	Black
253-501-30	Medium	Grey
253-502-10	Flood	White
253-502-20	Flood	Black
253-502-30	Flood	Grey
235-315-001	Anti dazzle shade	Black

Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
830	1400	13	A+
930	1300	14	A
840	1350	11	A++
940	1300	13	A+

### Note

Product available in other Kelvin temperatures by request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used. North American versions also available.